


Data Sheet

2025-03-03

Fiber Optic Duplex Patch Cord



Connector Side A



Cable cross-section scheme



Connector Side B

Connector Side A		Connector Side B	
LC/UPC Singlemode DX	Connector Description Design Specification Manufacturer Ferrule Operation Temperature Material of Ferrule Plug Cycles Typical Insertion Loss (IL) Typical Return Loss (RL) Bend Protection	LC/UPC Singlemode DX	Connector Description Design Specification Manufacturer Ferrule Operation Temperature Material of Ferrule Plug Cycles Typical Insertion Loss (IL) Typical Return Loss (RL) Bend Protection
IEC 61754-20, JIS C 5964-20		IEC 61754-20, JIS C 5964-20	
Seikoh Giken		Seikoh Giken	
Ø1.25mm, ceramics, axial suspended		Ø1.25mm, ceramics, axial suspended	
-40°C to +75°C		-40°C to +75°C	
Plastic / blue		Plastic / blue	
500		500	
≤ 0.12 dB (Class B)		≤ 0.12 dB (Class B)	
≥ 50 dB		≥ 50 dB	
red/black		red/black	

Cable			
Cable Type	I-V(ZN)H	Manufacturer	WEINERT
Number of Fibers	2x1	Fiber Class	OS2 Corning Ultra
Outer diameter	2.0mm	Cable Color	yellow
Cloak Material	FRNC	Minimal Bend Radius	30mm
Crush strength	400 N/dm	Pull Strength	400N
Cable Weight	9.0Kg/km	Operation Temperature	-5°C to +70°C